

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
15 September 2005 (15.09.2005)

PCT

(10) International Publication Number
WO 2005/085700 A1

(51) International Patent Classification⁷: **F16L 55/027**,
F15D 1/02, A61M 5/14, 5/168

(21) International Application Number:
PCT/NL2005/000097

(22) International Filing Date: 10 February 2005 (10.02.2005)

(25) Filing Language: Dutch

(26) Publication Language: English

(30) Priority Data:
1025624 3 March 2004 (03.03.2004) NL
1025697 11 March 2004 (11.03.2004) NL

(71) Applicant (for all designated States except US): **SOLVIST**
[NL/NL]; Bandholm 142, NL-2133 DN Hoofddorp (NL).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **LAMMERS, Leon**
[NL/NL]; Bandholm 142, NL-2133 DN Hoofddorp (NL).

(74) Agents: **VAN WESTENBRUGGE, Andries** et al.; Ned-
erlandsch Octrooibureau, P.O. Box 29720, NL-2502 LS
The Hague (NL).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ,
TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA,
ZM, ZW.


(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO,
SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN,
GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: FLOW RESTRICTION



(57) Abstract: Flow restriction to be fitted in a fluid line, consisting of a conduit part that has been produced from plastic by injection moulding and has been provided with a baffle closing the flow cross-section, wherein one or more openings have been made with the aid of a laser treatment. Each of these openings has a diameter of between 1 and 50 μm . It has been found that, when a large number of openings are used, if one of the openings becomes blocked for whatever reason this has hardly any effect on the total flow cross-sectional surface area. It is consequently possible to determine the flow conditions in the restriction very accurately and very reproducibly and consequently to establish the flow characteristics accurately. Such a flow restriction can be used, for example, in applications for dosing medication.

WO 2005/085700 A1